



G1 Amplifier Charger

Amplify your G1 experience!



FEATURES

- ◇ Fire Alert Indicator
- ◇ Horn Speaker
- ◇ Alert Lights
- ◇ 6 Pin DIN Jack
- ◇ Multi-Functional Charging for your
 - G1 Pager
 - Spare Battery
 - USB/Bluetooth

TECHNICAL SPECIFICATIONS

	ITEM	SPECS
Charging	Main Slot Charging	G1 Voice Pager
	Spare Charging Slot	Spare Ni-MH Battery (AAA)
	BT Charging Socket	BT Headset (USB-A-Type)
Power Supply	Adapter Input	100~240VAC/ 50~60 Hz
	Adapter Output	12Vdc/ 1.5A
	Normal Recharge Time	2.5 Hours
SPL	Alert Output	>= 106 dBSPL
External I/O	Audio Out	3.5 Earphone Jack
	Antenna Connector	BNC Jack
	Bluetooth Charging Port	USB A-Type
	Data Transfer	RS485 (DB-9 Female)
	DC Jack	12Vdc / 1.5A
	Terminal Block	4 Pin Socket (Horn Speaker)
	DIN Jack	6 Pin DIN Jack
Physical	Dimensions	162(L) x 115(W) x53(H) mm
External Antenna	Frequency Range	UHF Band 380~512MHz
		VHF Band 138~174MHz